



There are three versions available for use on Narrow, Standard and Broad Gauge track.

These were designed for use with the Master 35 Gas Impact Wrench but they can also be used with other power tools including the Maxim Pneumatic Rusty Clip Remover.

Using the Master Impact Wrench, Accessories and Tool Carrier together reduces vibration by over 30%, reduces manual handling, is easy and quick to use, improves operator comfort and increases productivity.

## FEATURES

- Adjustable arm for use with different weight tools.
- Can be assembled/dismantled in a few minutes without the use of tools.
- Use vertically or horizontally by changing Accessory
- Main Body can be locked down for safe transportation
- Insulated Wheels
- Can be inclined up to 5°
- Simple wheel brake

Ref.	Track Gauge	Notes
1750.0100	Standard 4' 8 1/2"	
1750.9999	Broad 5' 3" and 5' 6"	Same as Standard but with longer Bar
1750.0090	Narrow 3' 3 1/8" and 3' 6"	Standard Frame with a shorter Bar and a heavier Wheel for stability

An optional Deadman Handle Braking System can be fitted on request

## SPECIFICATION

Weight	Lbs
Wheel Assembly	22
Cross Bar	6 1/2
Main Frame	37 1/2
Total	66
The narrow Gauge version weighs an extra 12 1/4 lbs	

Dimensions Assembled	
Length	42 1/2"
Width	64"
Height	Open 34 1/4"
	Locked 17 1/4"



## ACCESSORIES Please Order separately as required

Ref.	Description
2801.7550	Wrench Bracket for vertical use on Chairscrews – Up to Serial Number ATE20 A105
2801.7565	Wrench Bracket for vertical use on Chairscrews – From Serial Number MA20 A001
2801.7560	Suspension Kit for horizontal use on Fishplates
2801.7515	Outtrigger Bar for Narrow Gauge 3' 3 1/8"/3' 6"
2801.7535	Heavy Wheel for Narrow Gauge 3' 3 1/8"/3' 6"
2801.7520	Outtrigger Bar for Standard Gauge 4' 8 1/2"
2801.7525	Outtrigger Bar for Broad Gauge 5' 3"/5' 6"

