

PROVEN RELIA

Master 35® Impact Wrench is powered by a New Generation low emission 63.4 c.c. Engine complying with EUR5 and EPA3 Standards which is a significant step towards de-carbonisation.

Because of its increased power the NEW Master 35 Impact Wrench will remove/fit most Chairscrews and Fishplate Nuts in under three seconds and using our Safety Quick Release Auger Attachment drill holes in Wooden Sleepers.

It is easily carried by one person, is operator friendly, can be used safely in all weather conditions, has good balance, easy to repair and because it is so fast reduces the potential harm of vibration exposure.

Use the Master 35 Impact Wrench mounted onto our Tool Carrier and reduce vibration by over 30%.

Impact Wrenches, Tool Carriers, Spare Parts and Accessories are available from stock held by our partner Distributors

throughout the World.









LOWER WEIGHT

INCREASED POWER

FASTER OPERATION

VIBRATION EXPOSURE LOW

LOW **EXHAUST EMISSION LEVELS**

LOW MAINTENANCE COST

ACCESSORIES

See reverse side of this leaflet

TECHNICAL SPECIFICATION

	Length	Height	Width	
DIMENSIONS	600mm	284mm	452mm	
ENGINE	Two stroke/cycle Special Airtec EMAK 63.4 c.c.			
	complying with EUR5 and EPA3 Standards			
POWER	3.4 HP 2.6 kW @ 7800rpm			
	16 to 32mm		to 32mm	
FASTENER TYPE	Bolt		diameter	
	Rectangular	all	sizes	
	Hexagon	Up	to 83mm	
	Square/Bi-S	quare Up	to 67mm	
NOISE LEVELS	Operation levels based on ISO3744 Acoustic Pressure (LpA) 101.7 dBA Power (LWA) 114.8 dBA Always wear ear protection			
SQUARE DRIVE	Standard 1"			
TORQUE RANGE	500 – 2,500Nm approximately			
	It is possible to generate higher torques			
	under special conditions. The Master			
	will loosen any screwed fastener			
	previously tightened by any other			
	Petrol/Gas Driven Impact Wrench.			

VIBRATION EXPOSURE

Vibration exposure is more important than vibration e.g. a low vibration machine which takes a long time to perform a task generates higher vibration exposure than a higher vibration machine which performs a task much more quickly.

The following data is based on practical on track testing carried out in the UK in February 2020.

Reduce vibration by fitting the Master 35 to our Tool Carrier Fishplates/Joint Bar Nuts - 2.25 seconds

		AV		LV	
	Vibration	Trigger Time Minutes	No of Fasteners	Trigger Time Minutes	No of Fasteners
Tightening	12.28m/s2	20	533	80	2133
Loosening	11.05m/s2	25	667	98	2613
Chairscrews/Lagscrews - 2.5 seconds					
		AV		LV	

Chan screws/Lagscrews - 2.3 Seconds						
		,	AV		LV	
	Vibration	n Trigger Time Minutes	No of Fasteners	Trigger Time Minutes	No of Fasteners	
Tightening	11.90m/s	2 21	504	85	2040	
Loosening	14.72m/s	2 14	336	55	1320	
WEIGHT		17.9 Kgs				

MASTER 35® ACCESSORIES

Part No.	Description				
	Master 35 Tool Carrier				
1750.0100	Standard Gauge				
1750.0090	Narrow Gauge				
1750.9999	Broad Gauge				
	-	airecrowe			
2801.7550	•	Master 35 Tool Carrier Accessory Vertical for Chairscrews			
2801.7560	Master 35 Tool Carrier Accessory Horizontal for F	-ishpiate Nuts			
вох	Metal Carrying Box with hinged lid and rubber strips on base				
AUG	Augering Attachment Quick Release – 9mm Hex E	uropean			
7.00	Auger Bits Scotch Nose Premium 245mm long	и ороши			
S10	10mm dia	S13	13mm dia		
S16	16mm dia	S17	17mm dia		
S18	18mm dia	S19	19mm dia		
S22	22mm dia	•			
GEISAUG	Augering Attachment Quick Release - Graffenstad	en Auger Bits			
GLIOAGG	Augering Attachment Quick Release - Granenstau	en Auger Dits			
	Auger Bits Graffenstaden Shank				
14G	14mm	16G	16mm dia		
18G	18mm				
	Impact Sockets 1" Square Drive				
454	28 x 21mm Rectangular Standard	454D	28 x 21mm Rectangular Deep		
454S	28 x 21mm Rectangular Thin Wall	511	24 x 20 Rectangular		
537	19mm Square	478	20mm Square		
463/1	21mm Square	453	22mm Square		
455	23mm Square	462	24mm Square		
508	25mm Square	561	26mm Square		
562 496	28mm Square 30mm Hex	712	30mm Hex Deep		
447	32mm Hex	495	32mm Hex Deep		
450	36mm Hex	466	36mm Hex Deep		
451	38mm Hex	465	38mm Hex Deep		
456	39mm Hex	457	39mm Hex Deep		
452	41mm Hex	458	41mm Hex Deep		
449 448	42mm Hex 46mm Hex	470 459	42mm Hex Deep 46mm Hex Deep		
			46IIIII Hex Deep		
SPADAP	Adaptor 1" Female to 23mm Square Quick Release	9			
	Quick Release Sockets 23mm Square Drive				
7821SQSP	21mm Square	7823SP	23mm Square		
7836SP	36mm Hex	7838SP	38mm Hex		
7841SP	41mm Hex	782420SP	24 x 20mm Rectangular		
782128SP	28 x 21mm Rectangular	782530SPBUT	35 x 23mm Rectangular		
	Extensions 1" Square Drive				
414	150mm long	407	200mm long		
408	250mm long	409	300mm long		
406	Universal Joint 1" Square Drive				
301	Rubber Ring	299	Steel Pin 49mm long		
299/1	Steel Pin 57mm long	299/2	Steel Pin 67mm long		
NOGO	Master 35® No Go Gauge				
.,,,,,,	Please contact us if the Accessory w		() ()		

Please contact us if the Accessory you need is not listed and we will supply it



For a free demonstration, quotation or more information on any of our products please contact :-



40 Couper Street, Glasgow, G4 0DL, Scotland, UK
Tel: 0044 141 552 5591 Fax: 0044 141 552 5064
E Mail: Enquiries@airtecinternational.co.uk
Website: www.airtecinternational.co.uk