

Increase Productivity



There are three versions available for use on Narrow, Standard and Broad Gauge track.

These were designed for use with the Master 35 Petrol Impact Wrench but they can also be used with other power tools including the Maxim Pneumatic Rusty Clip Remover.

Using the Master Impact Wrench, Accessories and Tool Carrier together reduces vibration by 30%, is easy and quick to use, improves operator comfort and increases productivity.

Ref.	Track Gauge	Notes
1750.0100	Standard 1435mm	
1750.9999	Broad 1600 and 1676mm	Same as Standard but with longer Bar
1750.0090	Narrow 1000 and 1067mm	Standard Frame with a shorter Bar and a heavier Wheel for stability

- ▶ Adjustable arm for use with different weight tools.
- ▶ Can be assembled/dismantled in a few minutes without the use of tools.
- ▶ Use vertically or horizontally by changing Accessory
- ▶ Main Body can be locked down for safe transportation
- ▶ Insulated Wheels
- ▶ Can be inclined up to 5°
- ▶ Simple wheel brake



AN OPTIONAL DEADMAN HANDLE BRAKING SYSTEM CAN BE FITTED ON REQUEST

Technical Specification

Weight		Kgs
Wheel Assembly		10.0
Cross Bar		3.0
Main Frame		17.0
Total		30.0
The narrow gauge version weighs an extra 5.8kgs		
Dimensions Assembled		mm
Length		1080
Width		1625
Height	Open	870
	Locked	440

Accessories Please order separately as required

Ref.	Description
2801.7550	Wrench Bracket for vertical use on Chairscrews – up to serial number ATE20 A105
2801.7565	Wrench Bracket for vertical use on Chairscrews – from serial number MA20 A001
2801.7560	Suspension Kit for horizontal use on Fishplates
2801.7515	Outrigger Bar for Narrow Gauge 1000/1067mm
2801.7535	Heavy Wheel for Narrow Gauge 1000/1067mm
2801.7520	Outrigger Bar for Standard Gauge 1435mm
2801.7525	Outrigger Bar for Broad Gauge 1600/1676mm

+44 (0) 141 552 5591

enquiries@airtecinternational.co.uk

40 Couper St, Glasgow, G4 0DL

www.airtecinternational.co.uk