

Increase Productivity



There are three versions available for use on Narrow, Standard and Broad Gauge track.

These were designed for use with the Master 35 Gas Impact Wrench but they can also be used with other power tools including the Maxim Pneumatic Rusty Clip Remover.

Using the Master Impact Wrench, Accessories and Tool Carrier together reduces vibration by 30%, is easy and quick to use, improves operator comfort and increases productivity.

Ref.	Track Gauge	Notes
1750.0100	Standard 4' 8 1/2"	
1750.9999	Broad 5' 3" and 5' 6"	Same as Standard but with longer Bar
1750.0090	Narrow 3' 3 1/8" and 3' 6"	Standard Frame with a shorter Bar and a heavier Wheel for stability

- ▶ Adjustable arm for use with different weight tools.
- ▶ Can be assembled/dismantled in a few minutes without the use of tools.
- ▶ Use vertically or horizontally by changing Accessory
- ▶ Main Body can be locked down for safe transportation
- ▶ Insulated Wheels
- ▶ Can be inclined up to 5°
- ▶ Simple wheel brake



AN OPTIONAL DEADMAN HANDLE BRAKING SYSTEM CAN BE FITTED ON REQUEST

Technical Specification

Weight		Lbs
Wheel Assembly		22
Cross Bar		6 1/2
Main Frame		37 1/2
Total		66
The narrow gauge version weighs an extra 12 3/4lbs		
Dimensions Assembled		Inches
Length		42 1/2
Width		64
Height	Open	34 1/4
	Locked	17 1/4

Accessories Please order separately as required

Ref.	Description
2801.7550	Wrench Bracket for vertical use on Lagscrews – up to serial number ATE20 A105
2801.7565	Wrench Bracket for vertical use on Lagscrews – from serial number MA20 A001
2801.7560	Suspension Kit for use on Joint Bar Nuts
2801.7515	Outrigger Bar for Narrow Gauge 3' 3 1/8"/3' 6"
2801.7535	Heavy Wheel for Narrow Gauge 3' 3 1/8"/3' 6"
2801.7520	Outrigger Bar for Standard Gauge 4' 8 1/2"
2801.7525	Outrigger Bar for Broad Gauge 5' 3'/5' 6"

+44 (0) 141 552 5591

enquiries@airtecinternational.co.uk

40 Couper St, Glasgow, G4 0DL

www.airtecinternational.co.uk